SUCTION CUPS 진공패드

SOLVAC

MF 40 & MF 50



FLAT SUCTION CUP WITH CLEATS

- ▶ Suitable for flat surfaces.
- ▶ Good stability and little inherent movement.
- ▶ Recommended when the lifting force is parallel to the surface of the object.

Order no.

MF 1 - 2 - 3

 $^{\scriptsize \textcircled{1}}$ VACUUM PAD $^{\varnothing}$

40 : Ø 40 50 : Ø 50 ② MATERIAL N: NBR

S : Silicon

CS: C.Silcon
U: Urethane

3 THREAD SIZE

X : NONE

18M: PF 1/8 " male 18F: PF 1/8 " female 14M: PF 1/4 " male

LIFTING FORCES & TECHNICAL DATA

Model	Lifting force vertical to the surface, kg, at vacuum level			Lifting force parallel to the surface, kg, at vacuum level			Volume (cm³)	Min.curve radius	Max. vertical movement	Weight (g)
	20-kPa	60-kPa	90-kPa	20-kPa	60-kPa	90-kPa	(GIII)	(mm)	(mm)	(9)
MF 40	2.04	4.08	5.1	1.5	2.5	3.0	4.8	52	2.5	5.5
MF 50	3.67	7.55	9.79	2.4	4.0	5.0	10	55	3.0	12